



DETAIL NOTES:

1. MATERIAL AND METHODS OF CONSTRUCTION SHALL BE IN CONFORMANCE WITH THE LATEST EDITION OF THE NEW YORK STATE DEPARTMENT OF TRANSPORTATION (NYSDOT) STANDARD SPECIFICATIONS FOR CONSTRUCTION AND MATERIALS..
2. ALL WORK SHALL CONFORM WITH SECTION 608 *SIDEWALK, DRIVEWAYS, AND BICYCLE PATHS* OF THE NYSDOT STANDARD SPECIFICATIONS. REFER TO NOTE NO. 1 ABOVE.
3. ALL CONCRETE SHALL BE 4,000 P.S.I. CLASS A CONCRETE. CONCRETE MATERIALS, PLACEMENT AND CONSTRUCTION SHALL CONFORM WITH SECTION 500 *PORTLAND CEMENT CONCRETE* OF THE NYSDOT STANDARD SPECIFICATIONS. REFER TO NOTE NO. 1 ABOVE.
4. REINFORCING STEEL FOR CONCRETE SHALL CONFORM WITH SECTION 556 *REINFORCING STEEL FOR CONCRETE STRUCTURES* OF THE NYSDOT STANDARD SPECIFICATIONS. REFER TO NOTE NO. 1 ABOVE, AND AS SPECIFICALLY CALLED OUT IN THE DRAWINGS.
5. SUBBASE MATERIAL SHALL CONFORM WITH SECTION 304 *SUBBASE COURSE* OF THE NYSDOT STANDARD SPECIFICATIONS. REFER TO NOTE NO. 1 ABOVE.
6. ALL EXPOSED SURFACES SHALL HAVE A BROOM TEXTURE FINISH WITH A TOOLED EDGE. UNLESS OTHERWISE SPECIFIED.
7. EXPANSION JOINTS SHALL BE INSTALLED AT ALL EXISTING IMMOVABLE OBJECTS, AT CONSTRUCTION COLD JOINTS, AND AS PER THE SPACING IDENTIFIED IN THIS DETAIL OR SPECIFICALLY CALLED OUT IN THE DRAWINGS.
8. NO JOINTS SHALL NOT BE SAW CUT. ALL JOINT SHALL BE AS PER THE STAMPED TEXTURE OR TOOLED. REFER TO NOTE NO. 6 ABOVE.
9. WHERE IT IS NECESSARY TO PLACE FILL FOR PURPOSE OF BRINGING THE SUBGRADE ELEVATION UP TO A SPECIFIED GRADE. THE FILL MATERIAL PLACED SHALL BE IN CONFORMANCE WITH SECTION 203 *EXCAVATION AND EMBANKMENT* OF THE NYSDOT STANDARD SPECIFICATIONS. REFER TO NOTE NO. 1 ABOVE.